



Product specifications	Lexmark XM1145	Lexmark XM3150
Print		
Display	Lexmark e-Task 4.3-inch (10.9 cm) color touch screen	Lexmark e-Task 7-inch (17.8 cm) color touch screen
Print speed: Up to ⁴	Black: 45 ppm	Black: 50 ppm
Time to first page: As fast as	Black: 6.5 seconds	
Print resolution	Black: 600 x 600 dpi, 1200 Image Quality, 2400 Image Quality, 1200 x 1200 dpi	
Memory / processor	Standard: 512 MB / Maximum: 2560 MB / Processor: Dual Core, 800 MHz	Standard: 1024 MB / Maximum: 3072 MB / Processor: Dual Core, 800 MHz
Hard disk	Option available	
Recommended monthly page volume ²	2000 - 12000 pages	2000 - 15000 pages
Maximum monthly duty cycle: Up to ³	100000 pages per month	150000 pages per month
Copying		
Copy speed: Up to ⁴	Black: 45 cpm	Black: 50 cpm
Time to first copy: As fast as	Black: 6.5 seconds	
Reduce / enlarge range	25 - 400%	
Scanning		
Duplex scan speed: Up to	A4/Ltr, Black: 18 / 19 sides per minute - A4 Ltr, Color: 8 / 9 sides per minute	A4/Ltr, Black: 20 / 21 sides per minute - A4/Ltr, Color: 13 / 14 sides per minute
Simplex scan speed: Up to	A4/Ltr, Black: 41 / 43 sides per minute - A4/Ltr, Color: 19 / 20 sides per minute	A4/Ltr, Black: 45 / 48 sides per minute - A4/Ltr, Color: 30 / 32 sides per minute
Scanner type / ADF scan	Flatbed scanner with ADF / RADF (Reversing Duplex) / 50 pages 20 lb or 75 gsm bond	
Optical scanning resolution	1200 x 600 ppi (black), 600 X 600 ppi (color)	
Faxing		
Modem speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps	
Supplies		
Laser cartridge yields	16,000 ¹ -page Extra High Yield Cartridge	
Cartridges shipping with product	5,000 ¹ -page Starter Return Program Toner Cartridge	7,500 ¹ -page Starter Return Program Toner Cartridge
Imaging unit estimated yield: Up to	60000 pages, based on 3 average letter/A4-size pages per print job and -5% coverage	
Paper handling		
Paper handling standard	Integrated duplex, 150-sheet output bin, 250-sheet input, 100-sheet multipurpose feeder	250-sheet output bin, Integrated duplex, 550-sheet input, 100-sheet multipurpose feeder
Paper handling optional	550-sheet tray, 250-sheet tray	Inline stapler, 250-sheet tray, 550-sheet tray
Paper input capacity: Up to	Standard: 350 pages 20 lb or 75 gsm bond / Maximum: 2000 pages 20 lb or 75 gsm bond	Standard: 650 pages 20 lb or 75 gsm bond / Maximum: 2300 pages 20 lb or 75 gsm bond
Paper output capacity: Up to	Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 150 pages 20 lb or 75 gsm bond	Standard: 250 pages 20 lb or 75 gsm bond / Maximum: 250 pages 20 lb or 75 gsm bond
Media types supported	Refer to the Card Stock & Label Guide, Plain Paper, Envelopes, Card Stock, Paper Labels, Transparencies	
Media sizes supported	A6, Oficio, Universal, Statement, Folio, DL Envelope, A4, 7 3/4 Envelope, 10 Envelope, 9 Envelope, A5, Executive, JIS-B5, Legal, Letter	
General		
Standard ports	Rear USB 2.0 Specification Hi-Speed Certified Port (Type A), One Internal Card Slot, Front USB 2.0 Specification Hi-Speed Certified Port (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000)	
Optional network ports / optional local ports	Internal MarkNet N8350 802.11b/g/n Wireless / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial	
Noise level: operating	Printing: 56 dBA / Copy: 56 dBA / Scan: 55 dBA	Printing: 55 dBA / Copy: 56 dBA / Scan: 55 dBA
ENERGY STAR	Yes	
Specified operating environment	Altitude: 0 - 2896 Meters (9,500 Feet), Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity	
Size (in. - H x W x D) / weight (lb.)	19.8 x 19.3 x 17.8 in. / 48 lb.	22.1 x 19.3 x 18.9 in. / 52 lb.



Family. Integrity. Trust.

Cannon IV, Inc.
6814 Hillsdale Court
Indianapolis, IN 46250
www.cannon4.com
(800) 825-7779
marketing@cannon4.com

¹ Yield at approximately 5% print coverage. ² "Recommended monthly page volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum monthly duty cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Print and copy speeds measured in accordance with ISO/IEC 24734, excludes first set of test documents. For more information see: www.lexmark.com/ISOspeeds.

© 2015 Lexmark and the Lexmark logo are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. All other trademarks are the property of their respective owners. ENERGY STAR® is a U.S. registered mark.

AirPrint and the AirPrint logo are trademarks of Apple Inc.