

Features

Dialing:

- Auto Dialer
 - One-touch: up to 32 stations (Including program keys)
 - Abbreviated: up to 168 stations
 - Maximum digits for telephone number: 36
- Program keys (up to 32)
- Directory Search Dialing
- Intelligent Redial
- Chain Dialing

Transmission:

- Quick Memory Transmission
- Multi-station Transmission (up to 210 stations)
- Automatic Memory Re-transmission
- Deferred Transmission
- Deferred Multi-station Transmission
- Priority Direct Transmission
- Automatic Cover Sheet
- ITU-T Sub-address Transmission

Reception:

- Distinctive Ring Detection (DRD)
- Junk Fax Filter
- Receive to Memory
- Substitute Reception
- Selective Reception
- Remote Reception
- Fax/Tel Auto Switch
- Collation Stack
- Automatic/Fixed Reduction
- Overlapping Print
- Header/Total Page Print

Polling:

- Polling/Multi-station Polling (up to 210 stations)
- Deferred Polling/Deferred Multi-Station Polling

Security / Special Communication:

- Password Transmission/Reception*1
- Fax Access Code (Fax Lock)
- PIN Code Access
- Fax Misdial Prevention
- Fax Forward

Convenience:

- LCD Display (16 x 2 lines)
- Edit File Mode with View Mode
- Number of memory job files
 - Max. 20 files: UF-5500
 - Max. 10 files: UF-4500
- Job Build (Max. 255 pages)

List Print:

- Communication Journal with image data
- Transaction Journal with view mode

Others:

- Multi-Tasking Operation
- 64-Level Halftone
- External TAM Interface
- Energy Saver
- Remote Diagnostics System (G3)
- Check & Call Function (G3)

UF-5500 / UF-4500 Specifications

Compatibility	ITU-T Group 3, ECM
Modem Speed	33.6 kbps - 2.4 kbps with automatic fallback
Coding Scheme	MH/MR/MMR
Transmission Speed*2	Approx. 3 sec.
Document Size	Max. 8.5" x 23.6" (216 mm x 600 mm) (with operator's assistance) Min. 5.0" x 5.8" (128 mm x 148 mm)
Effective Scanning Width	8.3" (212 mm)
Automatic Document Feeder Capacity*3	Up to 30 sheets (Letter)
Scanning Resolution (Fax)	Standard: 203 dots/inch x 98 lines/inch (8 dots/mm x 3.85 lines/mm) Fine: 203 dots/inch x 196 lines/inch (8 dots/mm x 7.7 lines/mm) Super Fine: 203 dots/inch x 391 lines/inch (8 dots/mm x 15.4 lines/mm)
Scanning Speed*4	Approx. 3 sec / page: UF-5500 (Letter, Standard mode) Approx. 4 sec / page: UF-4500 (Letter, Standard mode)
Recording Method	Laser printing on plain paper
Recording Paper Size	Letter / Legal*5 / A4, cut-sheet on plain paper
Effective Recording Width	8.2" (208 mm) (Letter)
Recording Paper Capacity	250 sheets (20 lb., 75 g/m ²)
Recording Resolution	Fax: Up to 203 dpi x 391 dpi Copy: Up to 203 dpi x 391 dpi Printer: Up to 600 dpi x 600 dpi (UF-5500 only)
Image Memory Capacity*6	8 MB (Approx. 480 pages): UF-5500 4 MB (Approx. 240 pages): UF-4500
Printer / Scanner Interface*7	USB 2.0, 10Base-T/100Base-TX Ethernet
Scanner Driver*7	TWAIN (Available via USB interface)
Scanning Resolution (PC)*7	Up to 600 dpi x 600 dpi
Power Requirements	AC 120 V, 60 Hz
Power Consumption	Max. Approx. 950 W Stand-by: 5.5 Wh
Dimensions (W x D x H)*8	16.5" x 18" x 11.7" (420 mm x 457 mm x 297 mm) (Excludes projections and optional paper cassette)
Weight*8	Approx. 25.4 lbs (Approx. 11.5 kg) (Excludes consumables and optional equipment)
UPC Code	885170022584



Options

- Legal Cassette (UE-409100)
UPC Code 885170049819

Consumables

- Toner Cartridge (UG-5591) 3,000 pages *9 UPC Code 885170026254
- Drum Cartridge (UG-5590) 6,000 pages UPC Code 885170026247

Note

- *1 Proprietary Panafax feature that will only work with selected Panafax fax machines.
- *2 Transmission time applies to memory transmission of text data using only ITU-T Image No. 1 between the same models at maximum modem speed. Transmission time may vary in actual usage. Standard public switched telephone networks can only support communications speeds of 28.8 Kbps or lower. Via PBX, transmission speed may fall back to a lower speed.
- *3 Using document thickness of 0.0024" - 0.0039".
- *4 Scanning speed is determined by measuring the feeding process time from the lead edge to the trail edge of a single page test chart. The scanning speed time does not include the time required for the leading edge of a document to reach the scanning point and page ejection sequence. Time required to store documents is not included as well.
- *5 Requires optional legal cassette.
- *6 Based on ITU-T Image No. 1 scanned in Standard mode.
- *7 Available on the UF-5500 only
- *8 Dimensions and weight are approximate.
- *9 Based on ITU-T Image No. 1 scanned in multiple copy mode. Yield may vary according to operating conditions and environment.

Dimensions*8



All other brand or product names are the property of their respective holders.
Design and specifications are subject to change without notice.

Genuine Toner Cartridge

Panasonic genuine toner cartridges and drum units will help ensure optimal machine performance and image quality. The use of genuine consumables will help protect your investment and maximize machine life by avoiding potential issues with compatible products.