

## KV-S1027C/ KV-S1057C Scanners – Higher speeds, lower maintenance

### KV-S1027C

#### FUNCTIONAL SPECIFICATIONS

##### IMAGE SENSOR TYPE

- Front side: Contact Image Sensor at 600 DPI
- Back side: Contact Image Sensor at 600 DPI
- Automatic black and white background reference

##### LIGHT SOURCE

- RGB LED

##### OPTICAL RESOLUTION

- 600 DPI (Main and sub feeding directions)

##### OUTPUT RESOLUTION

- Color: 24-bit
- Grayscale: 8-bit
- Monochrome: 1-bit

##### OUTPUT COLOR DEPTH

- Color: 24-bit
- Grayscale: 8-bit
- Monochrome: 1-bit

##### IMAGE PROCESSING FUNCTION

- Auto preview, Auto rescan, Image emphasis, Dynamic threshold, Automatic separation, Invert, White level from paper, Border removal, Despeckle, Auto rotation, Smoothing, Barcode detection

#### PERFORMANCE

##### SCANNING SPEED (A4, PORTRAIT)

- Simplex: 45 ppm
- Duplex: 90 ipm (200 DPI / 300 DPI) (Portrait)

##### ADF CAPACITY

- 100 Sheets: 21 lbs Letter/A4

##### DOCUMENT SIZE

- ADF minimum: 1.9" x 2.1"
- ADF maximum: 8.5" x unlimited

##### PAPER CAPACITY

- Thickness: 1.9 - 19.7 mils
- Weight: 5.4 - 91 lbs

##### INTERFACE

- USB 3.0 interface (Panasonic recommends a direct USB connection.)

#### PHYSICAL SPECIFICATIONS

##### POWER REQUIREMENTS

- AC 100 - 125 V, 50/60 Hz

##### POWER CONSUMPTION (OPERATING)

- Maximum (scanning): 35 W or less / .8 A (100-125 V)
- Minimum (ready): 8W or less
- Sleep Mode: 3W or less
- Power Off: 0.5 W or less

##### DIMENSIONS (WXDXH)

- 11.8" x 10.1" x 9.37"

##### WEIGHT

- 8.8 lbs

##### INBOX CONTENTS

- Power Cord, USB 3.0 Cable, Panasonic Software CD-ROM, Nuance PaperPort Installation CD-ROM, Quick Installation Guide, Mixed Batch Card Guide

##### BUNDLED SOFTWARE

- Panasonic Image Capture Plus, Nuance PaperPort 14 Installation CD-ROM, Panasonic User Utility, TWAIN Driver, ISIS Driver, WIA Driver

##### OPTIONS

- Network Scanning Adapter, Flatbed Scanner, Roller Exchange Kit, Roller Cleaning Paper, Carrier Sheet, Kofax VRS Elite Desktop 5.0 (V model)

##### OS SUPPORT

- |                            |             |
|----------------------------|-------------|
| ■ Windows XP SP3           | 32bit/64bit |
| ■ Windows Vista SP2        | 32bit/64bit |
| ■ Windows 7                | 32bit/64bit |
| ■ Windows 8                | 32bit/64bit |
| ■ Windows 8.1              | 32bit/64bit |
| ■ WindowsServer2003 SP2    | 32bit/64bit |
| ■ WindowsServer2003 R2 SP2 | 32bit/64bit |
| ■ WindowsServer2008 SP2    | 32bit/64bit |
| ■ WindowsServer2008 R2 SP1 | 64bit       |
| ■ WindowsServer2012        | 64bit       |

##### FEED DETECTION FEATURES

- Ultrasonic Double Feed Detection, Intelligent Double Feed Detection

##### OTHER FEATURES

- 100 Programmable Workflows

##### WARRANTY

3 year standard warranty including advance exchange

##### SERVICE OPTIONS

Professional installation and next business day onsite service available

### KV-S1057C

#### FUNCTIONAL SPECIFICATIONS

##### IMAGE SENSOR TYPE

- Front side: Contact Image Sensor at 600 DPI
- Back side: Contact Image Sensor at 600 DPI
- Automatic black and white background reference

##### LIGHT SOURCE

- RGB LED

##### OPTICAL RESOLUTION

- 600 DPI (Main and sub feeding directions)

##### OUTPUT RESOLUTION

- Color: 24-bit
- Grayscale: 8-bit
- Monochrome: 1-bit

##### OUTPUT COLOR DEPTH

- Color: 24-bit
- Grayscale: 8-bit
- Monochrome: 1-bit

##### IMAGE PROCESSING FUNCTION

- Auto preview, Auto rescan, Image emphasis, Dynamic threshold, Automatic separation, Invert, White level from paper, Border removal, Despeckle, Auto rotation, Smoothing, Barcode detection

#### PERFORMANCE

##### SCANNING SPEED (A4, PORTRAIT)

- Simplex: 65 ppm
- Duplex: 130 ipm (200 DPI / 300 DPI) (Portrait)

##### ADF CAPACITY

- 100 Sheets: 21 lbs Letter/A4

##### DOCUMENT SIZE

- ADF minimum: 1.9" x 2.1"
- ADF maximum: 8.5" x unlimited

##### PAPER CAPACITY

- Thickness: 1.9 - 19.7 mils
- Weight: 5.4 - 91 lbs

##### INTERFACE

- USB 3.0 interface (Panasonic recommends a direct USB connection.)

#### PHYSICAL SPECIFICATIONS

##### POWER REQUIREMENTS

- AC 100 - 125 V, 50/60 Hz

##### POWER CONSUMPTION (OPERATING)

- Maximum (scanning): 40 W or less / .8 A (100-125 V)
- Minimum (ready): 8W or less
- Sleep Mode: 3W or less
- Power Off: 0.5 W or less

##### DIMENSIONS (WXDXH)

- 11.8" x 10.1" x 9.37"

##### WEIGHT

- 8.8 lbs

##### INBOX CONTENTS

- Power Cord, USB 3.0 Cable, Panasonic Software CD-ROM, Nuance PaperPort Installation CD-ROM, Quick Installation Guide, Mixed Batch Card Guide

##### BUNDLED SOFTWARE

- Panasonic Image Capture Plus, Nuance PaperPort 14 Installation CD-ROM, Panasonic User Utility, TWAIN Driver, ISIS Driver, WIA Driver

##### OPTIONS

- Network Scanning Adapter, Flatbed Scanner, Roller Exchange Kit, Roller Cleaning Paper, Carrier Sheet, Kofax VRS Elite Desktop 5.0 (V model)

##### OS SUPPORT

- |                            |             |
|----------------------------|-------------|
| ■ Windows XP SP3           | 32bit/64bit |
| ■ Windows Vista SP2        | 32bit/64bit |
| ■ Windows 7                | 32bit/64bit |
| ■ Windows 8                | 32bit/64bit |
| ■ Windows 8.1              | 32bit/64bit |
| ■ WindowsServer2003 SP2    | 32bit/64bit |
| ■ WindowsServer2003 R2 SP2 | 32bit/64bit |
| ■ WindowsServer2008 SP2    | 32bit/64bit |
| ■ WindowsServer2008 R2 SP1 | 64bit       |
| ■ WindowsServer2012        | 64bit       |

##### FEED DETECTION FEATURES

- Ultrasonic Double Feed Detection, Intelligent Double Feed Detection

##### OTHER FEATURES

- 100 Programmable Workflows

##### WARRANTY

3 year standard warranty including advance exchange

##### SERVICE OPTIONS

Professional installation and next business day onsite service available