

Features

- Auto Dialer One-touch: up to 40 stations (including program keys)
Abbreviated: up to 300 stations
Maximum digits for telephone number: 36
- Program keys (up to 8 Programs)
- Multi-Tasking Operation
- Directory Search Dialing
- Fax Misdial Prevention
- Directory Sheet Print
- Intelligent Redial
- Chain Dialing
- Distinctive Ring Detection (DRD)
- Quick Memory Transmission
- Multi-station Transmission (up to 352 stations)
- Automatic Memory Retransmission
- Deferred Transmission
- Deferred Multi-station Transmission
- Priority Direct Transmission
- Job Build (Max. 255 pages)
- Edit File Mode with View Mode
- Automatic Cover Sheet
- Junk Fax Filter
- Receive to Memory
- Substitute Reception
- Selective Reception
- Number of memory job files (Max. 50 files)
- Fax Forward
- Polling/Multi-station Polling (up to 352 stations)
- Deferred Polling/Deferred Multi-Station Polling
- Confidential Mail Box *¹ (10 mail boxes)
- Password Transmission/Reception *¹
- ITU-T Sub-address Transmission
- Panasonic Super Smoothing (Fax/Copy)
- 64-Level Halftone
- Automatic/Fixed Reduction
- Overlapping Print
- Collation Stack
- Verification Stamp
- Communication Journal with image data
- Header/Total Page Print
- Transaction Journal with view mode
- Fax Access Code (Fax Lock)
- PIN Code Access
- Fax/Tel Auto Switch
- External TAM Interface
- Remote Reception
- LCD Display with Backlight (20 x 2 lines)
- Energy Saver
- Remote Diagnostics System (G3/Email)
- Check & Call Function (G3/Email)
- LDAP 2 Compatible
- SMTP Authentication
- APOP
- POP before SMTP

Standard Software

- Printer Driver
- Twain Scanner Driver
- PC-Fax software (Fax Driver/Panafax Desktop)
- Quick Image Navigator
- Phone Book Editor
- Configuration Editor
- Status Monitor



Handset Kit
UE-403186



Options

- Internet Fax Module (UE-404094)
- 250-sheet 2nd Paper Feed Module (UE-409090)
- Handset Kit (UE-403186)

Consumables

- All-In-One Print Cartridge (UG-5580)
9,000 pages *¹⁰

UF-6200 Specifications

Compatibility	ITU-T Group 3, ECM
Modem Speed	33.6 kbps - 2.4 kbps with automatic fallback
Coding Scheme	MH/MR/MMR
Transmission Speed* ²	Approx. 3 sec.
Document Size	Max. 10.1" x 78.7" (257 mm x 2000 mm) (with operator's assistance) Min. 5.8" x 5.0" (148 mm x 128 mm)
Effective Scanning Width	8.3" (212 mm)
Automatic Document Feeder	Up to 50 sheets (Letter)
Capacity* ³	
Scanning Resolution (Fax)	Standard: 203 dots/inch x 98 lines/inch (8 dots/mm x 3.85 lines/mm) Fine: 203 dots/inch x 196 lines/inch (8 dots/mm x 7.7 lines/mm) Super Fine: 203 dots/inch x 391 lines/inch (8 dots/mm x 15.4 lines/mm) 406 dots/inch x 391 lines/inch* ⁴ (16 dots/mm x 15.4 lines/mm)
Scanning Speed* ⁵	Approx. 2.8 sec. (Letter, Standard mode)
Recording Method	Laser printing on plain paper
Recording Paper Size	Letter / Legal / A4, cut-sheet on plain paper
Effective Recording Width	8.2" (208 mm) (Letter)
Recording Paper Capacity	250 sheets (20 lb., 75 g/m ²), Max. 500 sheets with optional Paper Feed Unit
Recording Resolution	Fax / Copy 406 dpi x 391 dpi Printer 600 dpi x 600 dpi
Image Memory Capacity* ⁶	8 MB (Approx. 480 pages)
Printer / Scanner Interface	USB 1.1
Scanner Driver	TWAIN
Scanning Resolution (PC)* ⁴	400 dpi x 400 dpi
Power Requirements	AC 120 V, 60 Hz
Power Consumption	Max. Approx. 470 W Sleep mode: 1.2 Wh
Dimensions (W x D x H)* ⁹	14.6" x 18.7" x 9.9" (370 mm x 474 mm x 253 mm)
Weight* ⁹	20 lb. (9.0 kg) (Excluding consumables and optional equipment)

Note

- *¹ Panafax proprietary features work only with selected Panafax machines.
- *² Transmission time applies to memory transmission of text data using only ITU-T Image No. 1 between the same models at maximum modem speed. Transmission time may vary in actual usage. Usually public telephone lines can only support communications speeds of 28.8 Kbps or lower. Via PBX, transmission speed may fall back to a lower speed.
- *³ Using 16lb, 60g/2 sheet. Set the documents as stairs shape.
- *⁴ Interpolated resolution (Optical Resolution: 203 dots/inch x 391 lines/inch)
- *⁵ Scanning speed applies to the feeding process from the top to the end of a single page test chart. The time for the feeding process does not include the time that it takes for the top edge of the page to reach the scanning point and page ejection. Time for entire storing process is not applied.
- *⁶ Speeds are contingent upon applications, machine configuration, and status. Individual speeds may vary.
- *⁷ In multiple copy mode excluding the first copy.
- *⁸ Based on ITU-T Image No. 1 scanned in Standard mode.
- *⁹ Dimensions and weight are approximate.
- *¹⁰ Based on ITU-T Image No. 1 scanned in multiple copy mode.
Yield may vary according to operating conditions and environment where the machine is installed.

Microsoft® and Windows® are registered trademarks of Microsoft Corporation.
All other brand or product names are the property of their respective holders.
Design and specifications are subject to change without notice.

Dimensions*⁹



Panasonic®

Panasonic Communications Company of North America
One Panasonic Way, Secaucus, NJ 07094
For a local dealer, please call 1-800-742-8086
panasonic.com/office



ISO 9001
Quality Management System

Our business processes which produce document, information and network products, from manufacturing to marketing, conform to ISO9001 Quality Management Systems standard. Design, development, manufacture, installation, repair and maintenance of document, information and network products, their associated devices and consumables. In addition, the plants outside Japan have acquired ISO9001 certification.