



Product specifications	Lexmark X792de	Lexmark X792dte	Lexmark X792dtfe
Printing			
Display	Lexmark e-Task 10-inch (25 cm) class color touch screen		
Print Speed: Up to	Black: 50 ppm / Color: 50 ppm		
Time to First Page: As fast as	Black: 8 seconds / Color: 8.5 seconds		
Print Resolution	Black: 1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi) / Color: 1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)		
Memory	Standard: 1024 MB / Maximum: 2048 MB		
Hard Disk	Included in configuration		
Recommended Monthly Page Volume ¹	2500 - 25000 pages		
Maximum Monthly Duty Cycle: Up to ²	150000 pages per month		
Copying			
Copy Speed: Up to	Black: 50 cpm / Color: 50 cpm		
Time to First Copy: As fast as	Black: 10 seconds / Color: 11 seconds		
Scanning			
Scanner Type / ADF Scan	Flatbed scanner with ADF / DADF (single pass Duplex)		
A4/Ltr Simplex Scan Speed: Up to	Black: 47 / 49 sides per minute / Color: 47 / 49 sides per minute		
Faxing			
Modem Speed	33.6 Kbps		
Supplies			
Cartridge(s) Shipping with Product	12,000-page Black and Color (CMY) Starter Return Program Print Cartridges		
Paper Handling			
Paper Input Capacity: Up to	Standard: 650 pages 20 lb or 75 gsm bond / Maximum: 2650 pages 20 lb or 75 gsm bond	Standard: 1750 pages 20 lb or 75 gsm bond / Maximum: 2300 pages 20 lb or 75 gsm bond	
Paper Output Capacity: Up to	Standard: 500 pages 20 lb or 75 gsm bond / Maximum: 1000 pages 20 lb or 75 gsm bond		Standard: 1000 pages 20 lb or 75 gsm bond / Maximum: 1000 pages 20 lb or 75 gsm bond
Media Types Supported	Glossy Paper, Polyester Labels, Paper Labels, Envelopes, Vinyl Labels, Refer to the Card Stock & Label Guide., Card Stock, Dual Web Labels, Outdoor Media, Integrated Labels, Transparencies, Plain Paper, Banner Paper		Glossy Paper, Polyester Labels, Paper Labels, Envelopes, Vinyl Labels, Refer to the Card Stock & Label Guide., Card Stock, Dual Web Labels, Outdoor Media, Integrated Labels, Transparencies, Plain Paper
Media Sizes Supported	C5 Envelope, 10 Envelope, Letter, B5 Envelope, Universal, Legal, A5, Folio, 7 3/4 Envelope, Statement, A4, 9 Envelope, Executive, DL Envelope, JIS-B5		
General Information			
Standard Ports	Ethernet 10/100/1000 BaseTX (RJ-45), Rear USB 2.0 Specification Hi-Speed Certified Port (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), Front USB 2.0 Specification Hi-Speed Certified port (Type A)		
Optional Network Ports / Optional Local Ports	External MarkNet N7020e Gigabit Ethernet, Internal MarkNet™ N8120 Gigabit Ethernet, Internal MarkNet™ N8130 Fiber Fast Ethernet, Internal MarkNet™ N8250 802.11b/g/n Wireless / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial		
Noise Level: Operating	Print: 52 dBA / Copy: 53 dBA / Scan: 54 dBA		
Specified Operating Environment	Altitude: 0 - 3048 Meters (10,000 Feet), Humidity: 8 to 80% Relative Humidity, Temperature: 16 to 32°C (60 to 90°F)		
Limited Warranty - See Statement of Limited Warranty	1-Year Onsite Service, Next Business Day		
Size (in. - H x W x D) / Weight (lb.)	32.5 x 22.0 x 20.0 in. / 161 lb.	47.4 x 24.05 x 25.9 in. / 247 lb.	47.4 x 41.55 x 25.9 in. / 283 lb.

¹"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ²"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

This is a Class A device according to the FCC Rules and international electromagnetic emissions standards. This device is not intended for use in residential or domestic environments due to potential interference to radio communications.