



Product specifications	Lexmark X925de
<b>Printing</b>	
Display	Lexmark e-Task 10-inch (25 cm) class color touch screen
Print Speed: Up to	Black: 30 ppm / Color: 30 ppm
Time to First Page: As fast as	Black: 9 seconds / Color: 11 seconds
Print Resolution	Black: 600 x 600 dpi, 1200 Image Quality / Color: 600 x 600 dpi, 1200 Image Quality
Memory	Standard: 512 MB / Maximum: 1536 MB
Hard Disk	Included in configuration
Recommended Monthly Page Volume <sup>3</sup>	5000 - 10000 pages
Maximum Monthly Duty Cycle: Up to <sup>2</sup>	200000 pages per month
<b>Copying</b>	
Copy Speed: Up to	Black: 30 cpm / Color: 30 cpm
Time to First Copy: As fast as	Black: 17 seconds / Color: 17 seconds
<b>Scanning</b>	
Scanner Type / ADF Scan	Flatbed scanner with ADF / RADF (Reversing Duplex)
A4/Ltr Duplex Scan Speed: Up to	Black: 12 sides per minute / Color: 12 sides per minute
A4/Ltr Simplex Scan Speed: Up to	Black: 33/ 32 sides per minute / Color: 33/ 32 sides per minute
<b>Faxing</b>	
Modem Speed	33.6 Kbps
<b>Supplies</b>	
Imaging Unit Estimated Yield: Up to <sup>1</sup>	30,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Cartridge(s) Shipping with Product	8,500-page Black High Yield Toner Cartridge, 7,500-page Color (CMY) High Yield Toner Cartridges
<b>Paper Handling</b>	
Paper Input Capacity: Up to	Standard: 450 pages 20 lb or 75 gsm bond / Maximum: 2100 pages 20 lb or 75 gsm bond
Paper Output Capacity: Up to	Standard: 250 pages 20 lb or 75 gsm bond / Maximum: 250 pages 20 lb or 75 gsm bond
Media Types Supported	Banner Paper, Refer to the Card Stock & Label Guide., Transparencies, Plain Paper, Labels, Envelopes, Card Stock
Media Sizes Supported	A6, Oficio, Universal, Statement, Letter, Legal, Ledger, JIS-B5, JIS-B4, Folio, Executive, DL Envelope, C5 Envelope, B5 Envelope, A5, A4, A3, 9 Envelope, 7 3/4 Envelope, 10 Envelope
<b>General Information</b>	
Standard Ports	Ethernet 10/100/1000 BaseTX (RJ-45), Rear USB 2.0 Specification Hi-Speed Certified Port (Type A), Front USB 2.0 Specification Hi-Speed Certified port (Type A), USB 2.0 Specification Hi-Speed Certified (Type B)
Optional Network Ports / Optional Local Ports	Internal MarkNet™ N8250 802.11b/g/n Wireless, Internal MarkNet™ N8130 Fiber Fast Ethernet, Internal MarkNet™ N8120 Gigabit Ethernet, External MarkNet N7020e Gigabit Ethernet / Internal 1284-B Bidirectional Parallel, Internal RS-232C serial
Noise Level: Operating	Print: 53 dBA / Copy: 54 dBA / Scan: 54 dBA
Specified Operating Environment	Altitude: 0 - 2300 Meters (7,545 Feet), Humidity: 20 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F)
Limited Warranty - See Statement of Limited Warranty	1-Year Onsite Service, Next Business Day
Size (in. - H x W x D) / Weight (lb.)	30.35 x 26.46 x 26.30 in. / 174.8 lb.

<sup>1</sup>Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>2</sup>Maximum Monthly Duty Cycle<sup>2</sup> is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>3</sup>Recommended Monthly Page Volume<sup>3</sup> is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

**This is a Class A device according to the FCC Rules and international electromagnetic emissions standards. This device is not intended for use in residential or domestic environments due to potential interference to radio communications.**