

Color laser multifunction product



Product specifications	Lexmark X950de	Lexmark X952dte	Lexmark X954dhe
Printing			
Display	Lexmark e-Task 10-inch (25 cm) class color touch screen		
Print Speed: Up to	Black: 45 ppm / Color: 40 ppm	Black: 50 ppm / Color: 45 ppm	Black: 55 ppm / Color: 50 ppm
Time to First Page: As fast as	Black: 5.5 seconds / Color: 7.7 seconds	Black: 5.2 seconds / Color: 7.7 seconds	Black: 5.0 seconds / Color: 7.2 seconds
Print Resolution	Black: 1200 x 1200 dpi, 2400 Image Quality / Color: 1200 x 1200 dpi, 2400 Image Quality		
Memory	Standard: 1024 MB / Maximum: 2048 MB		Standard: 2048 MB / Maximum: 2048 MB
Hard Disk	Included in configuration		
Recommended Monthly Page Volume ³	5000 - 33000 pages		
Maximum Monthly Duty Cycle: Up to ²	200000 pages per month	225000 pages per month	250000 pages per month
Copying			
Copy Speed: Up to	Black: 45 cpm / Color: 40 cpm	Black: 50 cpm / Color: 45 cpm	Black: 55 cpm / Color: 50 cpm
Time to First Copy: As fast as	Black: 7.1 seconds / Color: 10.4 seconds	Black: 6.8 seconds / Color: 10.4 seconds	Black: 6.4 seconds / Color: 9.9 seconds
Scanning			
Scanner Type / ADF Scan	Flatbed scanner with ADF / RADF (Reversing Duplex)		
A4/Ltr Duplex Scan Speed: Up to	Black: 38 / 37 sides per minute / Color: 38 / 37 sides per minute		
A4/Ltr Simplex Scan Speed: Up to	Black: 68 / 70 sides per minute / Color: 53 / 53 sides per minute	Black: 68 / 70 sides per minute / Color: 52 / 52 sides per minute	
Faxing			
Modem Speed	33.6 Kbps		
Supplies			
Photoconductor Estimated Yield: Up to ¹	115000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage		
Cartridge(s) Shipping with Product	11,000-page Color (CMY) Starter Toner Cartridges, 16,000-page Black Starter Toner Cartridge		
Paper Handling			
Paper Input Capacity: Up to	Standard: 620 pages 20 lb or 75 gsm bond / Maximum: 5140 pages 20 lb or 75 gsm bond	Standard: 2180 pages 20 lb or 75 gsm bond / Maximum: 4180 pages 20 lb or 75 gsm bond	Standard: 3140 pages 20 lb or 75 gsm bond / Maximum: 5140 pages 20 lb or 75 gsm bond
Paper Output Capacity: Up to	Standard: 500 pages 20 lb or 75 gsm bond / Maximum: 3750 pages 20 lb or 75 gsm bond		
Media Types Supported	Card Stock, Envelopes, Glossy Paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide.		
Media Sizes Supported	10 Envelope, 7 3/4 Envelope, A3, A4, A5, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Universal, Super Tabloid (12 x 18"), Oficio, A6		
General Information			
Standard Ports	USB 2.0 Specification Hi-Speed Certified (Type B), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified Port (Type A), Ethernet 10/100/1000 BaseTX (RJ-45)		
Optional Network Ports / Optional Local Ports	Internal MarkNet™ N8130 Fiber Fast Ethernet, Internal MarkNet™ N8250 802.11b/g/n Wireless / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel		
Noise Level: Operating	Print: 52 dBA / Copy: 55 dBA / Scan: 55 dBA		Print: 53 dBA / Copy: 55 dBA / Scan: 54 dBA
Specified Operating Environment	Altitude: 0 - 2500 Meters (8,200 Feet), Temperature: 10 to 32°C (50 to 90°F), Humidity: 15 to 85% Relative Humidity		
Limited Warranty - See Statement of Limited Warranty	1-Year Onsite Service, Next Business Day		
Size (in. - H x W x D) / Weight (lb.)	30.01 x 25.20 x 26.97 in. / 255.8 lb.	44.38 x 25.20 x 26.97 in. / 332.2 lb.	44.38 x 25.20 x 26.97 in. / 351.8 lb.

¹Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ²"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ³"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

This is a Class A device according to the FCC Rules and international electromagnetic emissions standards. This device is not intended for use in residential or domestic environments due to potential interference to radio communications.

© 2016 Lexmark and the Lexmark logo are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. All other trademarks are the property of their respective owners.

AirPrint and the AirPrint logo are trademarks of Apple Inc.

